



NOTE

1. TO BE USED AT END OR SIDE OF SIDEWALK WHERE GRADE DIFFERENCE WOULD CAUSE A PEDESTRIAN HAZARD, DURING LONG TERM CLOSURES OR PHASING OF SUBDIVISIONS.
2. ORANGE REFLECTORIZED TAPE TO BE APPLIED TO CROSS PLANKS HIGH INTENSITY RETRO REFLECTIVITY.
3. CROSS CEDAR PLANKS TO BE PAINTED WHITE.
4. TEMPORARY BARRIER TO BE INSTALLED 0.3m BEYOND END OF CONCRETE.
5. CAUTION SIGN TO BE INSTALLED AS PER OS 406 STREET SIGN LOCATION DETAIL AND ON BOULEVARD SIDE OF THE SIDEWALK.
6. CAUTION SIGN TO BE INSTALLED AT ALL SIDEWALK TERMINATIONS.
7. BLACK LETTERING ON ORANGE REFLECTIVE BACKGROUND, MINIMUM SHEETING – TYPE 1, ENGINEERING GRADE.

CITY OF OSHAWA

CHK'D: *S.S.*

APP'D: *S.H.*

DATE: JAN. 14, 2014

SIDEWALK TERMINATION AND TEMPORARY SIDEWALK BARRIER

REVISION No.

DATE: JAN. 14, 2014

OS-410