



Notes:

- ALL DIMENSIONS ARE IN MILLIMETERS.
- PROTECTIVE HOARDING FOR INDIVIDUAL TREES OR SMALL CLUMPS OF SIMILAR SIZED TREES TO BE POSITIONED IN ACCORDANCE WITH TABLE 1: TREE PROTECTION ZONES.
- PROTECTIVE FENCING FOR WOOD LOTS OR GROUPS OF TREES TO BE PROTECTED ARE TO BE POSITIONED AT A MINIMUM DISTANCE OF 1000mm BEYOND THE DRIP LINE OF EACH WOOD LOT OR GROUP(S) OF TREES TO BE PRESERVED.
- ALL TREE PROTECTION HOARDING SHALL BE IN PLACE AND MUST BE INSPECTED AND APPROVED BY THE CITY PRIOR TO ANY CONSTRUCTION ACTIVITIES. HOARDING SHALL REMAIN IN PLACE UNTIL ALL CONSTRUCTION ACTIVITIES HAVE CONCLUDED OR OTHERWISE INSTRUCTED BY LANDSCAPE ARCHITECT / CITY REPRESENTATIVE.
- ALL ARBORICULTURE WORK, INCLUDING PRUNING OF BRANCHES OR ROOTS SHALL BE COMPLETED BY A CERTIFIED ARBORIST.
- CONSTRUCTION ACTIVITIES, GRADE CHANGES, AND STORAGE OF EQUIPMENT AND MATERIALS ARE NOT PERMITTED WITHIN THE TREE PROTECTION ZONE.
- WHERE HIGH QUALITY SPECIMENS OCCUR ADJACENT TO AREAS SUBJECT TO CONSTRUCTION ACTIVITY, WOODEN CRIBBING SHALL BE INSTALLED TO PROTECT TRUCKS FROM DAMAGE IN THE EVENT THAT HEAVY EQUIPMENT BREAKS DOWN THE FENCE.
- HOARDING IS TO BE INSPECTED REGULARLY AND MAINTAINED BY THE CONTRACTOR.
- MAINTAIN EXISTING GRADES WITHIN THE TREE PROTECTION ZONE OF ALL TREES TO BE PRESERVED.
- THE AREA WITHIN THE TREE PROTECTION FENCING SHALL REMAIN UNDISTURBED AND FREE OF ALL DEBRIS, MATERIALS AND EQUIP.
- PRUNE DEAD WOOD ONLY UNLESS DIRECTED OTHERWISE BY THE CITY OR ASSIGNED DESIGNATE. DO NOT PRUNE LEADERS.
- IF APPLICABLE, WATERING AND FERTILIZING PROGRAMS SHALL BE MAINTAINED FOR THE DURATION OF THE CONSTRUCTION.
- REFER TO TREE PRESERVATION PLAN FOR TREE PROTECTION ZONE LOCATIONS.