



PROFILE DETAILS
N.T.S.

NOTE: * REVERSE GRADE DRIVEWAY ENTRANCES ONLY PERMISSABLE FOR COMMERCIAL, INDUSTRIAL, & MULTI-UNIT RESIDENTIAL AS PER CITY OF OSHAWA STORM SEWER CONNECTION BY-LAW 9-90.

S/W = SIDEWALK

RESIDENTIAL DRIVEWAYS – MINIMUM REQUIREMENTS			
DRIVEWAY MATERIAL	EXCAVATION (mm)	GRANULAR "A" (mm)	SURFACE MATERIAL (mm)
CRUSHED STONE	280	230	50 IN KIND
ASPHALT	280	230	50 HL3 OR HL3F AS DIRECTED BY CITY ENGINEER
PAVING STONE	280	195	25 BRICK SAND 60 PAVING STONE
CONCRETE	280	130	150 32MPa CONCRETE

NOTE:

1. MATERIAL DEPTHS FOR RESIDENTIAL DRIVEWAYS MAY NEED TO BE INCREASED WHERE SOIL CONDITIONS WARRANT OR WHERE MATCHING EXISTING CONDITIONS.
2. COMMERCIAL/INDUSTRIAL/MULTI-UNIT RESIDENTIAL – MATERIAL DEPTHS SHALL CONFORM TO SOILS REPORT RECOMMENDATIONS TO MEET DESIGN REQUIREMENTS FOR EXPECTED TRAFFIC VOLUME & VEHICULAR TYPE USE.
3. MEASUREMENTS IN METRES AND/OR MILLIMETRES UNLESS OTHERWISE SHOWN.
4. ALL MATERIALS SHALL CONFORM TO O.P.S.S. SPECIFICATIONS.

CITY OF OSHAWA

CHK'D: <i>S.S.</i>	DRIVEWAY SECTION	REVISION No. 4
APP'D: <i>G.H.</i>		DATE: FEB 2, 2022
DATE: FEB 2, 2022		OS-323